

©Bongri Calefacción, S.L. reserves all rights to the images that appear in this document. You may not reproduce or distribute part or all of the photographs and as the text. Both the brand as distinctive symbols are the exclusive property of the company. Violators will be prosecuted according to law.



Features

- Heating capacity with olive stone (m3): 782m3
- Tank capacity: 154 liters
- Metallic interior
- Cast-iron burner
- Autonomy (min-max): 13-40h
- Autonomy with olive stone (min-max): 9,8-32h
- Weight: 310kg
- Fume outlet diameter: 100mm
- Air inlet diameter: 80mm
- Multifuel
- Working pressure: 1,5bar
- Working maximum pressure: 2,5bar
- Closed expansion vessel: 8 l
- Maximum service temperature: 40/80°C
- Valve for drinking water
- Circulating pump
- Underfloor heating: 314*(m2)
- N° radiator elements: 225*
- Underfloor heating with olive stone: 313*(m2)
- N° radiator elements with olive stone: 224*
- Hermetic tank
- Management Heating / Sanitary Water
- S2:Security system: S2. Safety thermostat pellet, Safety thermostat water, Air flow switch, Safety valve 3 bar, Pressure setting valve
- Compatible accesories not included: VAL-02/VAL-04/CRONO-01/PE-130
- Multifuel boiler certified for burning pellet and olive stones
- Fully automatic cleaning of exchangers and burner
- Stainless steel support and scrapers
- New version of the base-cleaning system
- Black heat resistant paint and epoxy paint coating
- Stainless steel handles and cast-iron burner
- Thermally insulated chamber
- Combustion chamber window
- Automatic air vent included.
- Double door with vermiculite interior
- Exterior door with thermal insulation
- LCD Display with light for easy operation in dark room
- Height adjustable levelling feet
- Easy access fro cleaning and maintenance tasks
- * The calculation of radiators and underfloor heating has been determined according to normal conditions of a house insulation, located in a temperate zone. Aluminium radiator elements have been considered with a height of 60cm and a temperature difference of 50°, 120 kcal/element. Check characteristics (power) of the radiator.

Given the continued improvement of our products and improving our manufacturing process, size, aesthetics and product specifications are subject to change without prior notice from our company.

www.bronpi.com



la excelencia en el fuego