

Features

- Heating capacity (m3): 507 m3
- Heating capacity with olive stone (m3): 507m3
- Tank capacity: 74 l
- Metallic interior
- Autonomy (min-max): 9,8-32h
- Autonomy with olive stone: 9,6h
- Weight: 205kg
- Fume outlet diameter : 80mm
- Air inlet diameter : 60mm
- Multifuel
- Working pressure : 1,5bar
- Working maximum pressure : 2,5bar
- Closed expansion vessel: 8 l
- Maximum service temperature: 40/80°C
- Valve for drinking water
- Circulating pump
- Weekly programmer
- Automatic ignition
- Hermetic tank
- Underfloor heating: 200*(m2)
- N° radiator elements: 145*
- Underfloor heating olive stone: 200*(m2)
- N° radiator elements olive stone: 143*
- Management Heating / Sanitary Water
- Security system: S2. Safety thermostat pellet, Safety thermostat water, Air flow switch, Safety valve 3 bar, Pressure setting valve
- Compatible accessories not included: VAL-02/VAL-04/CRONO-01/PE-130
- Multifuel boiler certified for burning pellet and olive stones
- Stainless steel support and scrapers
- New version of the base-cleaning system
- Cast-iron burner
- Thermally insulated chamber
- Combustion chamber window
- Automatic air vent included
- LCD Display with light for easy operation in dark room
- Height adjustable levelling feet
- Ease of access to cleaning and maintenance tasks
- * The calculation of radiators and underfloor heating has been determined according to normal conditions of a house insulation, located in a temperate zone. Aluminium radiator elements have been considered with a height of 60cm and a temperature difference of 50°, 120 kcal/element. Check characteristics (power) of the radiator.

Given the continued improvement of our products and improving our manufacturing process, size, aesthetics and product specifications are subject to change without prior notice from our company.

www.bronpi.com

