


CARLOTA-MF

TERMOESTUFA MULTIFUEL CERTIFICADA PARA PELLET Y HUESO DE ACEITUNA.
 MULTIFUEL BACK BOILER CERTIFIED FOR BURNING PELLET AND OLIVE STONES.
 TERMOALAMANDRA MULTIFUEL CERTIFICADA PARA PELLET E CARROÇO DE AZEITONA.
 TERMOSTUFA MULTIFUELE CERTIFICATA PER PELLE E GUSCI DI OLIVE.
 THERMOPÖELE CERTIFIÉ POLYCOMBUSTIBLE A PELLETS ET NOYAU D'OLIVE


LIMPIEZA TOTALMENTE AUTOMATIZADA DE INTERCAMBIADORES Y QUEMADOR.
 FULLY AUTOMATIC CLEANING OF EXCHANGERS AND BURNER.
 LIMPEZA TOTALMENTE AUTOMÁTICA DOS PERMUTADOTES E DO QUEIMADOR.
 PULIZIA COMPLETAMENTE AUTOMATIZZATA DEGLI SCAMBIATORI E DEL BRUCIATORE.
 NETTOYAGE ENTIEREMENT AUTOMATISÉ DES ÉCHANGEURS ET DU BRÛLEUR.



VAL-02/VAL-04/CRONO-01/PE-130

Features

- Oasys
- Double Chamber System
- Clean Glass System
- Modulation System
- Model designed for easy access to maintenance service
- Programmable
- Power max: 23,3kw
- Power max with olive stone: 25,4kw
- Power max-min: 21,2-7,2kw
- Power with olive stone: 23,3kw
- Power transferred to the water: 20,3-6,9kw
- Power transferred to the water with olive stone: 20,3kw
- Efficiency: 91-96 %
- Efficiency with olive stone: 92%
- Consumption max-min: 4,9-1,5 kg/h
- Consumption with olive stone (kg/h): 5,6kg/h
- Power consumption: 150-500W



Given the continued improvement of our products and improving our manufacturing process, size, aesthetics and product specifications are subject to change without prior notice from our company.

www.bronpi.com



Features

- Heating capacity (m3): 507 m3
- Heating capacity with olive stone (m3): 507m3
- Tank capacity: 74 l
- Metallic interior
- Autonomy (min-max): 9,8-32h
- Autonomy with olive stone: 9,6h
- Weight: 205kg
- Fume outlet diameter : 80mm
- Air inlet diameter : 60mm
- Multifuel
- Working pressure : 1,5bar
- Working maximum pressure : 2,5bar
- Closed expansion vessel: 8 l
- Maximum service temperature: 40/80°C
- Valve for drinking water
- Circulating pump
- Weekly programmer
- Automatic ignition
- Hermetic tank
- Underfloor heating: 200*(m2)
- N° radiator elements: 145*
- Underfloor heating olive stone: 200*(m2)
- N° radiator elements olive stone: 143*
- Management Heating / Sanitary Water
- Security system: S2. Safety thermostat pellet, Safety thermostat water, Air flow switch, Safety valve 3 bar, Pressure setting valve
- Compatible accessories not included: VAL-02/VAL-04/CRONO-01/PE-130
- Multifuel boiler certified for burning pellet and olive stones
- Stainless steel support and scrapers
- New version of the base-cleaning system
- Cast-iron burner
- Thermally insulated chamber
- Combustion chamber window
- Automatic air vent included
- LCD Display with light for easy operation in dark room
- Height adjustable levelling feet
- Ease of access to cleaning and maintenance tasks
- * The calculation of radiators and underfloor heating has been determined according to normal conditions of a house insulation, located in a temperate zone. Aluminium radiator elements have been considered with a height of 60cm and a temperature difference of 50°, 120 kcal/element. Check characteristics (power) of the radiator.

Given the continued improvement of our products and improving our manufacturing process, size, aesthetics and product specifications are subject to change without prior notice from our company.

www.bronpi.com

