NOA











COMPREND UN ÉCHANGEUR DE CHALEUR-ACCUMULATEUR DE CHALEUR EN FONTE.



































582












WIFI KX 3C ANALIZATION KIT OPTIONAL REMOTE CONTROL


Features

- CANALIZATION KIT OPTIONAL
- Oasys Plus
- Double Chamber System
- Clean Glass System
- Modulation System
- Model designed for easy access to maintenance service
- Model Compatible with Kit Wifi
- Programmable
- Chamber overpressure valve
- Power max: 11,7kw
- Power max-min: 10,3-4,8kw
- Efficiency (%): 93-95%
- Consumption max-min (kg/h): 2,3-1,1kg/h
- Power consumption (W): 70-300W
- Heating capacity (m3): 258m3
- Tank capacity (Kg): 22kg
- Vermiculite interior
- Cast-iron burner
- Autonomy (h) (min-max): 9,6-20h
- Weight (kg): 122kg
- Fume outlet diameter (mm): 80mm
- Air inlet diameter (mm): 50mm
- Forced ventilation: 1x430
- Remote control or switchboard









Features

- S1:Security systems: Safety thermostat pellet, Air flow switch
- Compatible accesories not included:WIFI KIT; CANALIZATION KIT; OPTIONAL REMOTE CONTROL