FREE 6 VISION

Bio BRONPI

SDC | SC2 | SCL

kW Máx 6

kW	%		m³				kg	∅	
5-3	83-89	1,5-0,9	125	7,5		5-7	65	80	60

Features

- Double Combustion System
- Double Chamber System
- Clean Glass System
- Model designed for easy access to maintenance service
- Flame anti-return system
- Chamber overpressure valve
- Power max: 6kw
- Power max-min: 5-3kw
- Efficiency (%): 83-89%
- Consumption max-min (kg/h): 1,5-0,9kg/h
- Heating capacity (m3): 125m3
- Tank capacity (Kg): 7,5kg
- Metallic interior
- Autonomy (h) (min-max): 5-7h
- Weight (kg): 65kg
- Fume outlet diameter (mm): 80mm
- Air inlet diameter (mm): 60mm

2 years guarantee



Given the continued improvement of our products and improving our manufacturing process, size, aesthetics and product specifications are subject to change without prior notice from our company.

www.bronpi.com

BRONPI
la excelencia en el fuego

©Bronpi Calefacción, S.L. reserves all rights to the images that appear in this document. You may not reproduce or distribute part or all of the photographs and as the text. Both the brand as distinctive symbols are the exclusive property of the company. Violators will be prosecuted according to law.