HYDROTEX 23











150-450



143*









A 2,5-50

kg



VAL-02/VAL-04/ KIT WIFI

1,5

Features


FastOn

50


S2

- Oasys Plus
- Double Chamber System
- Load Level Sensor
- Modulation System
- Model designed for easy access to maintenance service
- Model Compatible with Kit Wifi
- Programmable
- Power max: 23kw
- Power transferred to the water: 20-5kw
- Efficiency: 82-87 %
- Consumption max-min: 4,8-1,2 kg/h
- Power consumption: 150-450W
- Heating capacity: 500 m3
- Tank capacity: 60
- Metallic interior
- Autonomy (min-max): 12,5-50h
- Weight: 250kg
- Fume outlet diameter: 100mm
- Air inlet diameter: 60mm





691 744





Given the continued improvement of our products and improving our manufacturing process, size, aesthetics and product specifications are subject

to change without prior notice from our company. www.bronpi.com

Features

- Working pressure: 1,5bar
- Working maximum pressure: 3bar
- Underfloor heating: 200*(m2)
- Nº radiator elements: 143*
- Closed expansion vessel: 6I
- Maximum service temperature: 40/80°C
- Valve for drinning water
- Circulating pump
- Hermetic tank
- Management Heating / Sanitary Water
- Security system: S2. Safety thermostat pellet, Safety thermostat water, Air flow switch, Safety valve 3 bar, Pressure setting valve
- Compatible accesories not included: VAL-02/VAL-04/KIT WIFI
- New patented heat exchange system.
- Cast-iron burner
- Thermally insulated chamber.
- Combustion chamber window.
- Automatic air vent included.
- Grafic LCD color Touch of 3.5?for programming and controlling the boiler.
- Height adjustable levelling feet.
- * The calculation of radiators and underfloor heating has been determined according to normal conditions of a house insulation, located in a temperate zone. Aluminium radiator elements have been considered with a height of 60cm and a temperature difference of 50°, 120 kcal/element. Check characteristics (power) of the radiator.



Given the continued improvement of our products and improving our manufacturing process, size, aesthetics and product specifications are subject to change without prior notice from our company.